

We claim:

1. A construction machine with a front window-locking device, comprising:

a cabin;

a front window for closing an opening at a front part of said cabin, said front window being adapted to be movable between a closed position of fully closing said opening and an opened position of fully opening said opening;

locking members rotatably mounted on a window frame of said front window, said locking members being adapted to secure said front window either in said closed position or in said opened position; and

engaging members provided in said cabin so as to face said locking members either in said closed position or in said opened position, wherein said locking members are coupled with said engaging members either in said closed position or in said opened position so as to overlap said engaging members in a thickness direction of said front window, and wherein surfaces for guidance making said locking members and said engaging members come into contact with each other on locking said front window are provided in one of said engaging members and said locking members.

2. The construction machine according to claim 1, wherein each of said locking members is provided with a knob for operation.

3. The construction machine according to claim 1, further comprising:

a handle provided on each of left and right sides of said front window for moving said front window between said closed position and said opened position, wherein each of said locking members is provided in the vicinity of said handle.

4. The construction machine according to claim 1, further comprising:

elastic members provided in the vicinity of said locking members for supporting said window frame by coming into elastic contact with a window glass of said front window.

5. The construction machine according to claim 1, further comprising:

link members pivotally mounted on said cabin through a supporting point of an upper part of the cabin, wherein said link members have engaging sections coupled with said locking members in said opened position and wherein said front window is adapted to be movable between the closed position and the opened position with support of said link members.

6. The construction machine according to claim 5, wherein each of said engaging sections has a hole for engaging.

7. The construction machine according to claim 6, wherein a surface for guidance is formed on the hole.